


BEDHEAD RECESSED



ANTI LIGATURE RECESSED RANGE



Anti Ligature Note: When correctly installed against wall, using 'Anti Pick' Mastic.

- IP54 – IK10++
- Two body dimensions / 100mm Recess Depth
- Robust Mild Steel Facia / Various decorative panel
- Optional VANDACOAT offering enhanced Corrosion/Vandal & Graffiti Resistant Coating System
- Opal or Clear Reeded Polycarbonate Diffuser
- Stainless Steel Torx Security Screw Fix
- Other RAL Colour options
- Microwave Motion Detection option
- Longlife 50,000 hrs Fluorescent options
- LED Option



Small



Large

DESCRIPTION

Robust anti - ligature recessed bedhead luminaire with either compact fluorescent lamps or 7.2 watt LED array and 220 – 240 volt 50Hz electronic driver. Luminaire can also be made suitable for exterior applications. Details on request. Concertina design to compensate for different wall thickness.

APPLICATION

General Hospitals, Care Homes, Psychiatric Hospitals, Corridors, Amenity Low Level Lighting etc

RANGE AVAILABLE

| Catalogue No. | Description | Length (mm) | Weight (Kg) | Dimensions |
|---------------|-----------------|-------------|-------------|------------|
| SMALL | | | | |
| BHR113 | 1x13w HF TC-DEL | 1ft/290mm | 3.5 Kg | |
| BHR118 | 1x18w HF TC-DEL | 1ft/290mm | 3.5 Kg | |
| BHR 8w | 8w LED DRIVER | 1ft/290mm | 3.5 Kg | |
| LARGE | | | | |
| BHR114 | 1x14w HF T5 | 2ft/650mm | 8.0 Kg | |
| BHR124 | 1x24w HF T5 | 2ft/650mm | 8.0 Kg | |
| BHR 23w | 23w LED DRIVER | 2ft/650mm | 8.0 Kg | |

LED Versions (Please refer to website for current technical specification)



| Wattage p/mtr | No LED's | Voltage | Lms | Weight (Kg) |
|---|----------|----------|--------------------|-------------|
| (Compromising of 10 qty x 100mm sections of 2.3w) | | | | |
| BHR46wLED | 60 | 24v/240v | 4500 } per lampway | 8.0 Kg |
| BHR23wLED | 60 | 24v/240v | 2100 } per lampway | 8.0 Kg |
| BHR8wLED | 6 | 24v/240v | 500 } per lampway | 3.8 Kg |
| BHR16wLED | 6 | 24v/240v | 1800 } per lampway | 3.8 Kg |

Various T5/T8 type LED Tubes on request
Available in colour temp 3000/4000/5000k

Suffix

| | |
|---------|--|
| /O | Opal Polycarbonate Diffuser |
| /P | Clear Reeded Polycarbonate Diffuser |
| /GRP | Glass Reinforced Panel |
| /W | White Paint Finish |
| /HFD | High Frequency Dimmable |
| /B | Black Paint Finish |
| /SD | Security Key |
| /M-Wave | Microwave Motion Detection option |
| /LIFE | Long Life Fluorescent option |
| /VCOAT | VANDACOAT Enhanced External Coating system |

*Various RAL colour options *Various Decorative Panel *Surface Version on Request



Cut out Dimensions
Small Body
265 x 135 mm
Large Body
615 x 135 mm