


BELMONT BOLLARD

EXTERIOR BOLLARD RANGE



- IP65
- Polycarbonate Head
- Clear Reeded or Opal Polycarbonate Lens
- Anodised Aluminium Louvre Stack in Clear Lens Only
- Heavy Gauge Moulded Tube (Non Corrosive)
- Root or Flange Mounted
- Compact PL Lamps options
- LED Option



DESCRIPTION

A range of resilient bollards. The tubular body is manufactured from 5mm thick moulded tube. It is an all polycarbonate head with a clear reeded or opal polycarbonate lens with aluminium louvre stack. High density plastic making it ideal for coastal & saline conditions

APPLICATION

Coastal locations, Commercial & Industrial Locations, Retail Parks, Residential Developments, Pathways Ideally suited to public circulation areas & exposed amenity lighting applications.

RANGE AVAILABLE

| Catalogue No. | Description | Weight (Kg) | Dimensions |
|---------------|-----------------|-------------|------------|
| BEL26 | 1x26w HF TC-DEL | 10.0 Kg | |
| BEL32 | 1x32w HF TC-TEL | 10.0 Kg | |
| BEL42 | 1x42w HF TC-TEL | 10.0 Kg | |

LED Versions (Please refer to website for current technical specification)

| Wattage | No LED's | mA | Lms | Weight (Kg) |
|-----------|----------|-----|------|-------------|
| BEL12wLED | 12 | 350 | 800 | 10.0 Kg |
| BEL18wLED | 12 | 500 | 1200 | 10.0 Kg |
| BEL24wLED | 12 | 700 | 2000 | 10.0 Kg |

Available in colour temp 3000/4000/5000K

Suffix

| | |
|------|-------------------------------|
| /P | Clear Reeded Lens |
| /O | Opal Lens |
| /RT | Root mounting version |
| /FL | Flange mounting plate version |
| /EM3 | Integral PL Emergency |

*Supplied with integral cone not louvre stack, Red/Yellow/Green or Blue LED options

*Various RAL colour options

