

BLOCK

VANDAL RESISTANT LIGHTING



- IP54 – IK10 ++
- Steel Fabricated Body
- Optional VANDACOAT offering enhanced Corrosion/Vandal & Graffiti Resistant Coating System
- Semi – Recessed
- Installation from Rear of Mounting Wall
- Rear Access for Easy Maintenance
- Clear Reeded Polycarbonate Diffuser
- Removable Gear Tray
- Stainless Steel Security Screws
- Microwave Motion Detection option
- LED Option



DESCRIPTION

A special vandal resistant atrium floodlight designed for use in high level cell block circulation areas. The fitting is installed from the rear of the mounting wall, with maintenance carried out from the rear for easy access. N.B. Installation of this luminaire is carried out entirely from the rear of the mounting wall.

APPLICATION

Used in HM Prisons and other secure establishments. Prison Areas e.g. Circulation Areas, Gymnasiums etc

RANGE AVAILABLE

Catalogue No.	Description	Weight (Kg)	Dimensions
BLK70S	70w SON	9.0 Kg	
BLK100S	100w SON	9.0 Kg	
BLK150S	150w SON	9.0 Kg	
BLK70MH	70w HIPE	9.0 Kg	
BLK100MH	100w HIPE	9.0 Kg	
BLK150MH	150w HIPE	9.0 Kg	

LED Versions (Please refer to website for current technical specification)

Wattage	No LED's	mA	Lms	Weight (Kg)
BLK24wLED	24	700	2500	9.0 Kg
BLK48wLED	24	1400	4800	9.0 Kg

Available in colour temp 3000/4000/5000K

Suffix

/P	Clear Reeded Diffuser
/O	Opal Diffuser
/W	White Paint Finish
/B	Black Paint Finish
/SD	Security Driver
/M-Wave	Microwave Motion Detection option
/VCOAT	VANDACOAT Enhanced External Coating system

