


# BOSTON FLAT TOP BOLLARD



## VANDAL RESISTANT BOLLARD RANGE



- IP65 – IK10 ++
- Cast Aluminium Flat Head
- Clear Polycarbonate Lens
- Anodised Aluminium Louvre Stack
- Heavy Gauge Steel Tube, Root or Flange Mounted
- Optional VANDACOAT offering enhanced Corrosion/Vandal & Graffiti Resistant Coating System
- Discharge or Compact PL Lamp options
- Black Paint Finish as standard
- Various RAL colour options on request
- Longlife 50,000 hrs Fluorescent options
- LED Option



### DESCRIPTION

A robust decorative bollard with clear polycarbonate lens & aluminium louvre stack, with robust alloy flat top. Root or flange plate mount options. Optional overall heights on request.

### APPLICATION

Commercial & Industrial Locations, Retail Parks, Residential Developments, Pathways Ideally suited to public circulation areas & exposed amenity lighting applications.

### RANGE AVAILABLE

Catalogue No.	Description	Weight (Kg)	Dimensions
BOSF50S	50w SON	13.0 Kg	
BOSF70S	70w SON	13.0 Kg	
BOSF50MH	50w Metal Halide, HIPE	13.0 Kg	
BOSF70MH	70w Metal Halide, HIPE	13.0 Kg	
BOSF26	26w HF/TC-DEL	12.5 Kg	
BOSF32	32w HF/TC-TEL	12.5 Kg	
BOSF42	42w HF/TC-TEL	12.5 Kg	

### LED Versions (Please refer to website for current technical specification)

Wattage	No LED's	mA	Lms	Weight (Kg)
BOSF12wLED	12	350	900	13.0 Kg
BOSF18wLED	12	500	1400	13.0 Kg
BOSF24wLED	12	700	2200	13.0 Kg

Available in colour temp 3000/4000/5000K

### Suffix

/RT	Root Mounting Version
/FL	Flange Mounting Plate Version
/EM3	Integral Emergency - PL lamps only
/180°	180° Light Baffle
/LIFE	Long Life Fluorescent option
/VCOAT	VANDACOAT Enhanced External Coating system

\*Other RAL colour options available on request

