

BOSTON STAINLESS STEEL BOLLARD



VANDAL RESISTANT BOLLARD RANGE



- IP65 – IK10 ++
- Stainless Steel Flat Head
- Clear Polycarbonate Lens
- Anodised Aluminium Louvre Stack
- Heavy Gauge Stainless Steel Tube
- Root or Flange Mount
- Discharge or Compact PL Lamp options
- Longlife 50,000 hrs Fluorescent options
- LED Option



DESCRIPTION

A robust decorative stainless steel bollard with clear polycarbonate lens & aluminium louvre stack, with robust stainless steel flat top. Root or flange plate mount options. Optional overall heights on request.

APPLICATION

Commercial & Industrial Locations, Retail Parks, Residential Developments, Pathways Ideally suited to public circulation areas & exposed amenity lighting applications.

RANGE AVAILABLE

Catalogue No.	Description	Weight (Kg)	Dimensions
BOSS50S	50w SON	13.0 Kg	
BOSS70S	70w SON	13.0 Kg	
BOSS50MH	50w Metal Halide, HIPE	13.0 Kg	
BOSS70MH	70w Metal Halide, HIPE	13.0 Kg	
BOSS26	26w HF/TC-DEL	12.5 Kg	
BOSS32	32w HF/TC-TEL	12.5 Kg	
BOSS42	42w HF/TC-TEL	12.5 Kg	

LED Versions (Please refer to website for current technical specification)

Wattage	No LED's	mA	Lms	Weight (Kg)
BOSS12wLED	12	350	900	13.0 Kg
BOSS18wLED	12	500	1400	13.0 Kg
BOSS24wLED	12	700	2200	13.0 Kg

Available in colour temp 3000/4000/5000K

Suffix

/RT	Root Mounting Version
/FL	Flange Mounting Plate Version
/EM3	Integral Emergency - PL lamps only
/180°	180° Light Baffle
/LIFE	Long Life Fluorescent option

