




COMET

EXTERIOR LIGHTING



- IP65 – IK10
- Robust Exterior Wallpack
- All Injection Polycarbonate Moulded Body & Lens
- Clear Reeded Polycarbonate Lens
- Microwave Motion Detection option
- Longlife 50,000 hrs Fluorescent options
- LED Option



DESCRIPTION

A range of exterior IP65 wallpack are suitable for many external lighting applications. Available in black.

APPLICATION

External Perimeter Lighting, Wall Mounted, Amenity Area Luminaire

RANGE AVAILABLE

Catalogue No.	Description	Weight (Kg)	Dimensions
CMT70S	70w SON	3.5 Kg	
CMT70MH	70w HIPE	3.5 Kg	
CMT32	1x32w HF TC-TEL	2.7 Kg	
CMT42	1x42w HF TC-TEL	2.7 Kg	

LED Versions (Please refer to website for current technical specification)

Wattage	No LED's	mA	Lms	Weight (Kg)
CMT16wLED	60	500	1500	2.7 Kg
CMT23wLED	60	700	2100	2.7 Kg
CMT26wLED	72	700	2500	2.7 Kg

note EM3 version c/w 4 x 1w LED
Available in colour temp 3000/4000/5000K

Suffix

/EM3	Integral 3 hr Emergency (2D & PL versions only)
/PC	Integral Photocell
/M-Wave	Microwave Motion Detection option

