

COMMANDER SMALL



AMENITY / MAINS AND EMERGENCY LIGHTING RANGE



- IP65 – IK10 ++
- Fully Welded Metal Base
- Optional VANDACOAT offering enhanced Corrosion/Vandal & Graffiti Resistant Coating System
- Opal or Clear Reeded Polycarbonate Diffuser
- Removable Gear Tray
- Stainless Steel Torx Captive Screw
- Conduit BESA Fixing
- Recessed Flange Version Optional
- Microwave Motion Detection option
- Longlife 50,000 hrs Fluorescent options
- LED Option



DESCRIPTION

Rectangular slim design. Bulkhead luminaire with 4 No Torx stainless steel screws. Removable high frequency gear tray for low energy fluorescent lamps, maintained & non maintained emergency versions. Conduit entry. Recessed version available.

APPLICATION

Interior & Exterior usage, Lobbies, Corridors, Multi Storey Car Parks, Stairs, Toilets etc

RANGE AVAILABLE

| Catalogue No. | Description | Weight (Kg) | Dimensions |
|---------------|-------------------------------------------|-------------|------------|
| COMS108 | 1x8w HF T5 240V mains bulkhead | 2.5 Kg | |
| COMS208 | 2x8w HF T5 240V mains bulkhead | 2.5 Kg | |
| COMS108N3 | 1x8w HF T5 3 hour non-maintained bulkhead | 3.0 Kg | |
| COMS208N3 | 2x8w HF T5 hour non-maintained bulkhead | 3.0 Kg | |
| COMS108M3 | 1x8w HF T5 3 hour maintained bulkhead | 3.0 Kg | |
| COMS208S3 | 2x8w HF T5 3 hour sustained bulkhead | 3.0 Kg | |

LED Versions (Please refer to website for current technical specification)


| Wattage | No LED's | V | Lms (P/200mm) | Weight (Kg) |
|------------|----------|----|---------------|-------------|
| COMS8wLED | 6 | 24 | 500 | 2.5 Kg |
| COMS16wLED | 6 | 24 | 1500 | 2.5 Kg |

note EM3 version c/w 4 x 1w LED
Available in colour temp 3000/4000/5000K

Suffix

| | |
|---------|--------------------------------------------|
| /W | White Metal Work |
| /B | Black Metal Work |
| /PC | Integral Photocell |
| /O | Opal Diffuser |
| /P | Clear Reeded Diffuser |
| /RM | Recess Mount option cut out 380mm x 155mm |
| /SS | Security Screws |
| /SD | Security Driver |
| /M-Wave | Microwave Motion Detection option |
| /LIFE | Long Life Fluorescent option |
| /VCOAT | VANDACOAT Enhanced External Coating system |

*Eyelid option on request



 Cut out 380mm x 155mm
Recessed version

