

DISCO SURFACE

AMENITY LIGHTING RANGE



- IP20
- Ceiling or Wall Mounted
- Spun Aluminium Body
- Opal or Clear Prismatic Polycarbonate Diffuser
- Removable High Frequency Gear Tray
- Other RAL Colours On Request
- Microwave Motion Detection option
- Longlife 50,000 hrs Fluorescent options
- LED Option



DESCRIPTION

Slimline circular luminaire for interior decorative applications & is suitable for wall or ceiling mounting giving downward light. Opal or prismatic polycarbonate diffuser held with spring clips.

APPLICATION

Corridors, Care Homes, Entrances, Stair Wells, Shopping Centres.

RANGE AVAILABLE

Catalogue No.	Description	Weight (Kg)	Dimensions
DSS282D	1X28w2D HF TC-DD	4.0 Kg	
DSS382D	1x38w2D HF TC-DD	4.0 Kg	
DSS224	2x24w HF TC-L	4.0 Kg	
DSS324	3x24w HF TC-L	4.0 Kg	
DSS22	1x22w HF T5 (T16R)	4.0 Kg	
DSS40	1x40w HF T5 (T16R)	4.0 Kg	
DSS55	1x55w HF T5 (T16R)	4.0 Kg	
DSS122/55	1x22/1x55w HF T5 (T16R)	4.0 Kg	

LED Versions (Please refer to website for current technical specification)

Wattage	No LED's	mA	Lms	Weight (Kg)
DSS16wLED	60	500	1500	4.0 Kg
DSS23wLED	60	700	2100	4.0 Kg
DSS26wLED	72	700	2500	4.0 Kg

note EM3 version c/w 4 x 1w LED
Available in colour temp 3000/4000/5000K

Suffix

/HFD	High Frequency Dimmable
/DP	Dish Prismatic Controller
/DO	Dish Opal Diffuser
/DF	Dish Frosted Diffuser
/EM3	Integral Maintained Emergency
/NL	Night Light
/W	White Paint Finish
/S	Silver Paint Finish
/M-Wave	Microwave Motion Detection option
/LIFE	Long Life Fluorescent option

*Other RAL colours available on request

