




# ENDURANCE EYELID

## AMENITY LIGHTING



- IP65 – IK10
- Black Body
- All Polycarbonate Body & Diffuser
- Opal Diffuser or Prismatic Diffuser
- Wall Mounted, Black Eyelid
- Stainless Steel Torx Security Screws
- Removable High Frequency Gear Tray
- Microwave Motion Detection option
- Longlife 50,000 hrs Fluorescent options
- LED Options



### DESCRIPTION

360 mm diameter circular sealed luminaire with opal deep dish diffuser with black eyelid. Electronic high frequency control gear for compact fluorescent lamps.

### APPLICATION

External amenity lighting situations. Wall mounted.

### RANGE AVAILABLE

Catalogue No.	Description	Weight (Kg)	Dimensions
ENDX282D	28w 2D HF TC-DD	2 Kg	
ENDX382D	38w 2D HF TC-DD	2 Kg	
ENDX552D	55w 2D HF TC-DD	2 Kg	
ENDX218	2x18w HF TC-DEL	2 Kg	
ENDX226	2x26w HF TC-DEL	2 Kg	
ENDX132	1x32w HF TC-TEL	2 Kg	
ENDX142	1x42w HF TC-TEL	2 Kg	

**LED Versions** (Please refer to website for current technical specification)

Wattage	No LED's	mA	Lms	Weight (Kg)
ENDX11wLED	60	350	1000	2.0 Kg
ENDX16wLED	60	500	1500	2.0 Kg
ENDX23wLED	60	700	2100	2.0 Kg
ENDX26wLED	72	700	2500	2.0 Kg

note EM3 version c/w 4 x 1w LED  
Available in colour temp 3000/4000/5000K

#### Suffix

/MW	Micro Wave Presence Detector
/EM3	Integral Maintained Emergency – 28,38 & 2x18w only
/PC	Integral Photo-Cell
/SS	Fitted with Security Screws
/SD	Security Screwdriver
/M-Wave	Microwave Motion Detection option
/LIFE	Long Life Fluorescent option

