

ENDURANCE

AMENITY LIGHTING



- Anti – Ligature Note: Anti Ligature when correctly installed & using 'Anti Pick' Mastic against ceiling.
- IP65 – IK10 ++
- Black or White Body
- All Polycarbonate Body & Diffuser
- Opal or Clear Prismatic Diffuser
- Stainless Steel Torx Security Screws
- Removable High Frequency Gear Tray
- Microwave Motion Detector Option
- Longlife 50,000 hrs Fluorescent options
- LED Options



DESCRIPTION

360 mm diameter circular sealed luminaire with optional opal or clear prismatic deep dish diffuser. Electronic high frequency control gear for compact fluorescent lamps.

APPLICATION

Car Parks, Entrances, Supermarkets, Corridors, Toilets, Public Areas, Canopies, and many other Internal or external amenity lighting situations. Wall or ceiling mounted.

RANGE AVAILABLE

Catalogue No.	Description	Weight (Kg)	Dimensions
END282D	28w 2D HF TC-DD	2 Kg	
END382D	38w 2D HF TC-DD	2 Kg	
END552D	55w 2D HF TC-DD	2 Kg	
END218	2x18w HF TC-DEL	2 Kg	
END226	2x26w HF TC-DEL	2 Kg	
END132	1x32w HF TC-TEL	2 Kg	
END142	1x42w HF TC-TEL	2 Kg	

LED Versions (Please refer to website for current technical specification)

Wattage	No LED's	mA	Lms	Weight (Kg)
END11wLED	60	350	1000	2 Kg
END16wLED	60	500	1500	2 Kg
END23wLED	60	700	2100	2 Kg
END26wLED	72	700	2500	2 Kg

note EM3 version c/w 4 x 1w LED
Available in colour temp 3000/4000/5000K

Suffix

/W	White Body
/B	Black Body
/P	Prismatic Diffuser
/O	Opal Diffuser
/MW	Micro Wave Presence Detector
/EM3	Integral Maintained Emergency – 28,38 & 2x18w only
/PC	Integral Photo-Cell
/SS	Fitted with Security Screws
/SD	Security Screwdriver
/M-Wave	Microwave Motion Detection option
/LIFE	Long Life Fluorescent option

