

ENERGY LED UNIVERSAL



RECESSED LED DOWNLIGHT RANGE



- IP20/44
- Latest LED Technology
- Cast Aluminium Heatsink for Optimum Thermal Control
- Supplied with Remote Gear
- Highly Polished Reflector
- Robust Suspension Brackets
- Finished in White, Black or Metallic Silver
- Various Accessories available



DESCRIPTION

Recessed downlight incorporating the latest LED technology. White, Black or Metallic silver finish as standard. Various accessories available

APPLICATION

Offices, Corridors, Foyers, Restaurants, Shopping Malls, Showrooms etc




ATT1



ATT2



ATT3



ATT4

RANGE AVAILABLE

Catalogue No.	Description	Dist (°)	LED Colour (k)	Dimensions
NRGU 9LED	9w LED & driver	40°	2700k	
NRGU 9LED	9w LED & driver	40°	3000k	
NRGU 9LED	9w LED & driver	40°	4000k	
NRGU 18LED	18w LED & driver	40°	2700k	
NRGU 18LED	18w LED & driver	40°	3000k	
NRGU 18LED	18w LED & driver	40°	4000k	

Suffix

/ATT1	Clear Attachment
/ATT2	Frosted Attachment
/ATT3	Drop Glass - Outer Frosted Attachment
/ATT4	Halo Attachment

