GARRISON











VANDAL RECESSED RANGE













- IP54 IK10++
- Robust Steel Body & Frame
- Sealed Front Bezel with Rear Access (Through Wall)
- Captive Clear Stippled or Opal Polycarbonate Flat Panel
- Stainless Steel Security Screws (Rear Door Fixing)
- Removable High Frequency Gear Tray
- Microwave Motion Detection option
- Longlife 50,000 hrs Flourescent options
- LED Option



DESCRIPTION

A range of special vandal resistant recessed cell lights which are totally sealed in the wall or ceiling, 3mm solid steel bezel & robust captive diffuser panel. The fitting has rear entry for easy maintenance. Stainless steel security screws on rear. Concertina design to compensate for different wall thickness.

APPLICATION

Police stations, Prisons Psychiatric Hospitals, Schools, Under Canopies, Public Areas, Rail Way Stations etc

RANGE AVAILABLE

Catalogue No.	Description	Weight (Kg)	Dimensions
GAR218	2x18w HF TC-L	11 Kg	
GAR224	2x24w HF TC-L	11 Kg	

LED Versions (Please refer to website for current technical specification)

Clear Stippled Diffuser

Wattage p/mtr	No LED's	Voltage	Lms	Weight (Kg)
(Compromising of 10 qty \times 1 GAR23wLED	00mm sections of 2.3w) 60	24v/240v	2100 } per lampway	8.0 Kg

Voltago

Various T5/T8 type LED Tubes on request Available in colour temp 3000/4000/5000k

Suffix

Wattago n/mtr

/0	Opai Folycarbonate billusei
/GRP	Glass Reinforced Panel
/HFD	High Frequency Dimmable
/EM3	3 hour Remote Maintained Emergency
/NL	Night Light
/SD	Security Driver
/M-Wave	Microwave Motion Detection option
/LIFE	Long Life Fluorescent option

No LEDio

