

HIRAK T5 LOW BAY

SURFACE RANGE



- IP20
- 4 or 6 Lamp T5/TC-L High Output Options
- High Grade Polished Aluminium Reflectors
- Seperate Switching Options
- Excellent Efficiency & Photometric Performance
- Wire Guard (Optional)
- Clear Polycarbonate Panel (Optional)
- Motion Detection (Optional)
- Longlife 50,000 hrs Fluorescent options
- LED Options



DESCRIPTION

Steel Body with supporting reflector clad with mirror bright anodised aluminium for optimum light output. High Frequency control gear for T5 or TC-L fluorescent lamps.

APPLICATION

Suitable for Warehouses/Production, High Ceilings or for typical Aisle Lighting, Sports Hall Fitting etc

RANGE AVAILABLE

Catalogue No.	Description	Weight (Kg)	Dimensions
HIR454	4x54w HF T5	7.0 Kg	
HIR654	6x54w HF T5	9.0 Kg	
HIR480	4x80w HF T5	8.0 Kg	
HIR680	6x80w HF T5	10.0 Kg	
HIR455	4x55w HF TC-L	6.0 Kg	
HIR480	4x80w HF TC-L	6.0 Kg	

LED Versions (Please refer to website for current technical specification)

Wattage p/mtr	No LED's	Voltage	Lms
(Compromising of 10 qty x 100mm sections of 2.3w) HIR23wLED	60	24v/240v	2100 } per lampway

Various T5/T8 type LED Tubes on request
Available in colour temp 3000/4000/5000k

Suffix

/HFD	High Frequency Dimmable
/WG	Wire Guard
/P	Clear Polycarbonate Panel
/EM3	Integral Emergency
/M-WAVE	Microwave Detector
/LIFE	Long Life Fluorescent option

