

LIBERTY DROP INDIRECT OPAL RECESSED MODULAR



- IP20
- Central Curved Opal Diffuser
- Injection Moulded End Caps (white or chrome)
- Powder Coated Paint Finish
- Suitable for 15/25 Exposed 'T' Grid Ceilings
- Optional Extra Bezel for Plasterboard Ceilings
- High Frequency Control Gear
- Microwave Motion Detection option
- Longlife 50,000 hrs Fluorescent options
- LED Option



DESCRIPTION

Flagship range of recessed luminaires designed to meet present day standards. Curved opal translucent diffuser providing both direct & indirect lighting 'gull' reflector directing light across the ceiling. LED option on request & long life fluorescent options.

APPLICATION

Commercial Office Lighting, Meeting Rooms, Computer Rooms, Retail Areas, Reception, Medical Areas etc

RANGE AVAILABLE

Catalogue No.	Description	Weight (Kg)	Dimensions
LIBDO155	1x55w HF TC-L	6.2 Kg	
LIBDO255	2x55w HF TC-L	6.2 Kg	
LIBDO214	2x14w HF T5	6.2 Kg	
LIBDO224	2x24w HF T5	6.2 Kg	

LED Versions (Please refer to website for current technical specification)

Wattage p/mtr	No LED's	Voltage	Lms	Weight (Kg)
(Compromising of 10 qty x 100mm sections of 2.3w) LIBDO23wLED	60	24v/240v	2100 } per lampway	6.3 Kg

LED flat panel on request
Various T5/T8 type LED Tubes on request
Available in colour temp 3000/4000/5000k

Suffix

/HFD	High Frequency Dimmable Gear
/EM3	3 Hour Maintained Emergency
/ATT	Plasterboard Mounting Kit
/ECW	White End Caps
/ECC	Chrome End Cap
/M-Wave	Microwave Motion Detection option
/LIFE	Long Life Fluorescent option

