

# LIBERTY INDIRECT LOUVRE

## RECESSED MODULAR



- IP20
- Central Curved Perforated Metal Diffuser Containing CAT2 Aluminium Louvre
- Direct / Indirect Lighting Control
- Fabricated Steel Body
- Powder Coated Paint Finish
- Suitable for 15/25 Exposed 'T' Grid Ceiling
- Optional Extra Bezel for Plasterboard Ceilings
- High Frequency Control Gear
- Microwave Motion Detection option
- Longlife 50,000 hrs Fluorescent options
- LED Option



### DESCRIPTION

A range of recessed modular fluorescent luminaires is suitable for applications where aesthetic appearance and light control are important providing comfort direct / indirect lighting. LED option on request & long life fluorescent options.

### APPLICATION

Commercial Office Lighting, Meeting Rooms, Computer Rooms, Retail Areas, Reception, Medical Areas etc

### RANGE AVAILABLE

Catalogue No.	Description	Weight (Kg)	Dimensions
LIBL236	2x36w HF TC-L	4.4 Kg	
LIBL240	2x40w HF TC-L	4.4 Kg	
LIBL255	2x55w HF TC-L	4.4 Kg	

### LED Versions (Please refer to website for current technical specification)

Wattage p/mtr	No LED's	Voltage	Lms	Weight (Kg)
(Compromising of 10 qty x 100mm sections of 2.3w)				
LIBL23wLED	60	24v/240v	2100 } per lampway	4.4 Kg

Various T5/T8 type LED Tubes on request  
Available in colour temp 3000/4000/5000k

### Suffix

/HFD	High Frequency Dimmable Gear
/EM3	3 hour Maintained Emergency
/ATT	Plasterboard Mounting Kit
/M-Wave	Microwave Motion Detection option
/LIFE	Long Life Fluorescent option

