



**Anti Ligature Note:** When correctly installed against ceiling, using 'Anti Pick' Mastic.

- IP65 – IK10++
- All Polycarbonate Body & Lens
- Clear Reeded or Opal Lens
- Surface or Recessed Mount
- Stainless Steel Torx Security Screws
- Can be used as Independent Emergency Luminaire
- 7 watt GU10 Fluorescent Reflector Lamp
- Longlife 50,000 hrs Fluorescent options
- LED & Emergency LED versions



Recessed



Surface

### DESCRIPTION

IP65 anti ligature tough all polycarbonate construction, clear reeded or opal flush fit lens held captive with 3 No stainless steel Torx screws. Surface or recessed mount. Compact fluorescent GU10 reflector lamp. LED version available for use as emergency or night light (info available upon request).

### APPLICATION

Hospitals, Psychiatric Units, Bedded Ward Areas, Corridors, Above Emergency Exit Doors, Utility Rooms etc

### RANGE AVAILABLE

Catalogue No.	Description	Weight (Kg)	Dimensions
NIT7	NIT 1x 7 watt 240volt GU10 Reflector Lamp	0.5 Kg	
NIT3	1x3w LED	0.5 Kg	
NIT3/EM3	1x3w LED 3 hour Maintained or Non Maintained	0.5 Kg	
NIT4	1x4w LED	0.5 Kg	
NIT8	1x8w LED	0.5 Kg	

### Suffix

/SM	Surface Mounted
/RM	Recess Mounted
/EM3	Integral 3 hour Emergency – LED version only (Remote Gear)
/SS	Stainless Steel Security Screws
/SD	Security Driver
/LIFE	Long Life Fluorescent option

