


EXTERIOR LIGHTING RANGE



- IP65 - IK10++
- Fabricated Treated Steel Body
- Optional VANDACOAT offering enhanced Corrosion/Vandal & Graffiti Resistant Coating System
- Internal Gear Compartment
- 60 mm Spigot Entry
- Black Primed Polyester Texture Paint Finish
- Clear Reeded Polycarbonate Lens
- Flat Glass Bezel
- Specular Aluminium Reflector
- LED Option



DESCRIPTION

Symmetrical distribution amenity lighting luminaire suitable for mounting heights between 6 & 10 meters. Spigot brackets available for single and twin luminaire applications. Also available with Flat Glass panel.

APPLICATION

Road Lighting, Car Parks, General External Lighting etc

RANGE AVAILABLE

Catalogue No.	Description	Weight (Kg)	Dimensions
ORK70S	70w SON	5 Kg	
ORK100S	100w SON	5 Kg	
ORK150S	150w SON	5 Kg	
ORK250S	250w SON	5 Kg	
ORK70MH	70w Metal Halide	5 Kg	
ORK100MH	100w Metal Halide	5 Kg	
ORK150MH	150w Metal Halide	5 Kg	
ORK250MH	250w Metal Halide	5 Kg	

LED Versions (Please refer to website for current technical specification)

Wattage	No LED's	mA	Lms	Weight (Kg)
ORK23wLED	60	700	2100	4.3 Kg
ORK26wLED	72	700	2500	4.5 Kg
ORK24wLED/HO	24	700	2500	4.5 Kg
ORK48wLED/HO	24	1400	4800	4.5 Kg

Available in colour temp 3000/4000/5000K

Suffix

/GL	Flat Glass
/PC	Integral dusk to dawn photocell
/ORK T/S	Single Bracket Spigot
/ORK T/T	Twin Bracket Spigot
/LIFE	Long Life Fluorescent option
/VCOAT	VANDACOAT Enhanced External Coating system

*Refer to page 48 for spigot adaptors

*Other RAL colour options on request

