



OXFORD

VANDAL RESISTANT SURFACE FLUORESCENT RANGE



- IP44/54 – IK10++
- Metal End Cap
- Clear Prismatic Polycarbonate Controller
- Vandal Resistant Design
- Removable High Frequency Gear-Tray
- Stainless Steel Security Screws
- White Metalwork as standard
- Other RAL Colour Options



DESCRIPTION

A shallow surface mounted robust luminaire incorporating a clear reeded extruded polycarbonate diffuser, supported along its length by the luminaire body & held captive by metal end cap. Fixed by stainless steel security screws. Removable high frequency gear tray.

APPLICATION

Car Parks, Medium Security Areas, Pedestrian Walk Ways, Schools, Public Areas, Local Authority Areas etc

RANGE AVAILABLE

Catalogue No.	Description	Length	Weight (Kg)	Dimensions	
OXF114	1 x 14w HF T5	2ft/ 600mm	2.5 Kg		
OXF128	1 x 28w HF T5	4ft/1200mm	3.5 Kg		
OXF154	1 x 54w HF T5	4ft/1200mm	3.5 Kg		
OXF135	1 x 35w HF T5	5ft/1500mm	4.0 Kg		
OXF149	1 x 49w HF T5	5ft/1500mm	4.0 Kg		
OXF214	2 x 28w HF T5	2ft/ 600mm	2.5 Kg		
OXF228	2 x 28w HF T5	4ft/1200mm	3.5 Kg		
OXF254	2 x 54w HF T5	4ft/1200mm	3.5 Kg		
OXF235	2 x 35w HF T5	5ft/1500mm	4.0 Kg		
OXF249	2 x 49w HF T5	5ft/1500mm	4.0 Kg		
Suffix					
/HFD	High Frequency Dimmable Gear				
/P	Prismatic Polycarbonate Diffuser				
/EM3	3 hour Maintained Emergency				
/NL	Nite Lite				
/SD	Security Key				
/IP54	IP54 Version				

*Other RAL colours on request

*Stainless Steel version available for special applications