

# REFLEX 410

## ANTI-LIGATURE SURFACE RANGE



**Anti Ligature Note:** When correctly installed against ceiling, using 'Anti Pick' Mastic.

- IP44/65 - IK10 ++
- 410mm Diameter High Grade Aluminium Body
- Clear Prismatic Frosted or Opal Polycarbonate Diffuser (which removes without disturbing Anti Pick Mastic)
- Stainless Steel Security Screws
- Removable High Frequency Gear Tray
- Other RAL Colours Available
- Optional VANDACOAT offering enhanced Corrosion/Vandal & Graffiti Resistant Coating System
- Microwave Motion Detection option
- Longlife 50,000 hrs Fluorescent options
- LED Option



### DESCRIPTION

Slim Profile circular surface luminaire. Spun aluminium 410mm diameter body, captive opal or prismatic polycarbonate diffuser. Removable electronic high frequency gear tray. 4 No stainless steel torx security screws. Diffuser removes without need to disturb Anti-Pick Mastic for ease of maintenance. LED Option & long life fluorescent options.

### APPLICATION

Psychiatric Hospitals, Secure Unit, Schools, Toilets, Corridors, Public Buildings, Lobbies etc

### RANGE AVAILABLE

Catalogue No.	Description	Weight (Kg)	Dimensions
RFXS162D	1x16w 2D HF TC-DD	4.0 Kg	
RFXS282D	1x28w 2D HF TC-DD	4.0 Kg	
RFXS382D	1x38w 2D HF TC-DD	4.0 Kg	
RFXS218w	2x18w HF TC-DEL	4.0 Kg	
RFXS226w	2x26w HF TC-DEL	4.0 Kg	
RFXS22	1x22w HF T5 (T16R)	4.0 Kg	

**LED Versions** (Please refer to website for current technical specification)

Wattage	No LED's	mA	Lms	Weight (Kg)
RFXS16wLED	60	500	1500	4.0 Kg
RFXS23wLED	60	700	2100	4.0 Kg
RFXS26wLED	72	700	2500	4.0 Kg

note EM3 version c/w 4 x 1w LED  
Available in colour temp 3000/4000/5000K

### Suffix

/HFD	High Frequency Dimmable
/DP	Dish Prismatic Diffuser
/DO	Dish Opal Diffuser
/DF	Dish Frosted Diffuser
/W	White Paint Finish
/EM3	Integral Maintained Emergency
/NL	Night Light
/SD	Security Driver
/IP65	IP65 Gasket (optional)
/M-Wave	Microwave Motion Detection option
/LIFE	Long Life Fluorescent option
/VCOAT	VANDACOAT Enhanced External Coating system

\*Various RAL options    \*Anodised colour options available

