


SOFTSPREAD

SURFACE UPLIGHT RANGE



- IP20
- Perforated Curve Profile Metal Body with Opal Inner Lining
- Frosted Ribbed Diffuser Attachment (optional)
- White Paint Finish
- Up – Down Light, Wall Fixture
- High Frequency Control Gear
- White or Chrome End Caps
- Longlife 50,000 hrs Fluorescent options



DESCRIPTION

Wall mounted adjustable luminaire with perforated cover. Available in two sizes with option of other attachments. Small Body 1x18w Large Body 1x55w / 2x55w. Available long life fluorescent options.

APPLICATION

Offices, Corridors, Foyers, Hotels, Reception Areas etc

RANGE AVAILABLE

Catalogue No.	Description	Weight (Kg)	Dimensions
SMALL SFD118 SFD126	Body Only	1x18w HF TC-L 4.5 Kg	135mm 320 / 595mm
LARGE SFD155 SFD255		1x26w HF TC-DEL 4.5 Kg	
Suffix Ribbed Frosted Diffuser Attachment Only SFDS SFDL	Small Diffuser Large Diffuser	4.5 Kg 4.5 Kg	Adjustable
Perforated Basket Attachment SFPS SFPL	Small Basket Large Basket		
End Caps SFCW SFCC	White End Cap Chrome End Cap		
/LIFE	Long Life Fluorescent option		

