

# SOLAR BOLLARD

## EXTERIOR BOLLARD RANGE



- IP54 – IK10
- Clear Polycarbonate Lens
- Root or Flange Mount
- Optional VANDACOAT offering enhanced Corrosion/Vandal & Graffiti Resistant Coating System
- LED 1 or 3 WATT Solar Powered
- Internal Opal Prism Optics
- UK Design / Manufacture
- Ideal for Both Southern / Northern Hemisphere
- Integral Circuit & Battery Pack, lasts upto 3 days continuous use from 1 x Full Charge
- Various RAL colour options



### DESCRIPTION

A decorative solar powered bollard with clear polycarbonate lens. Root or flange plate mount options. Integral Plush Optics, Solar Panel and Battery Control Circuit. Optional overall heights on request.

### APPLICATION

Ideally suited to public circulation areas & exposed amenity, Car Park, walkway lighting applications where an electrical supply is not present or would be expensive to install.

### RANGE AVAILABLE

Catalogue No.	Description	Weight (Kg)	Dimensions
SOL1x1w	1 Watt White LED	10 Kg	
SOL1x3w	3 Watt White LED	10 Kg	
<b>Suffix</b>			
/RT	Route Mounting Version		
/FL	Flange Mounting Plate Version		
/F	Flat Top Option		
/D	Dome Top Option		
/VCOAT	VANDACOAT Enhanced External Coating system		

