

SOLAR

EXTERIOR LIGHTING



- IP65 – IK10
- All Injection Moulded Base & Diffuser
- Clear Reeded Polycarbonate Black Top Diffuser
- Removable High Frequency Gear Tray / Reflector
- Energy Efficient Compact PL Fluorescent Lamps
- Stainless Steel Security Screws (optional)
- Microwave Motion Detection option
- Longlife 50,000 hrs Fluorescent options
- LED Option



DESCRIPTION

All injection moulded black body luminaire with captive screw front visor. Removable high frequency electronic control gear tray for low energy compact fluorescent lamps.

APPLICATION

External Low Level Amenity Lighting, Under Canopy etc

RANGE AVAILABLE

Catalogue No.	Description	Weight (Kg)	Dimensions
SLR282D	1x28w2D HF TC-DD	3.0 Kg	
SLR382D	1x38w2D HF TC-DD	3.0 Kg	
SLR132	1x32w HF TC-TEL	3.0 Kg	
SLR142	1x42w HF TC-TEL	3.0 Kg	

LED Versions (Please refer to website for current technical specification)

Wattage	No LED's	mA	Lms	Weight (Kg)
SLR16wLED	60	500	1500	3.0 Kg
SLR23wLED	60	700	2100	3.0 Kg
SLR26wLED	72	700	2500	3.0 Kg

note EM3 version c/w 4 x 1w LED
Available in colour temp 3000/4000/5000K

Suffix

/P	Clear Reeded Black Top Diffuser
/EM3	Integral 3 Hour Emergency
/PC	Integral Dusk to Dawn Photo-Cell
/SS	Security Screw
/SD	Security Key
/M-Wave	Microwave Motion Detection option
/LIFE	Long Life Fluorescent option

