

# TROJAN SMALL



## AMENITY / MAINS AND EMERGENCY LIGHTING RANGE



- IP65 – IK10
- Injection Moulded Polycarbonate Luminaire
- Opal or Clear Reeded Diffuser
- Removable High Frequency Gear Tray
- Stainless Steel Torx Captive Screw
- Conduit Entry
- Black or White Base
- Microwave Motion Detection option
- Longlife 50,000 hrs Fluorescent options
- LED Options



### DESCRIPTION

Rectangular slim design. Bulkhead luminaire with 4 No Torx stainless steel screws. Removable high frequency gear tray for low energy fluorescent lamps, maintained & non maintained emergency versions. Conduit entry. Recessed version available.

### APPLICATION

Interior & Exterior usage, Lobbies, Corridors, Multi Storey Car Parks, Stairs, Toilets etc

### RANGE AVAILABLE

Catalogue No.	Description	Weight (Kg)	Dimensions
TROS118	1x18w HF TC-DEL 240v Mains	2.0 Kg	
TROS126	1x26w HF TC-DEL 240v Mains	2.0 Kg	
TROS108	1x8w HF T5 240V mains bulkhead	2.0 Kg	
TROS208	2x8w HF T5 240V mains bulkhead	2.0 Kg	
TROS108N3	1x8w HF T5 3 hour non-maintained bulkhead	2.2 Kg	
TROS208N3	2x8w HF T5 3 hour non-maintained bulkhead	2.2 Kg	
TROS108M3	1x8w HF T5 3 hour maintained bulkhead	2.2 Kg	
TROS208S3	2x8w HF T5 3 hour sustained bulkhead	2.2 Kg	

### LED Versions (Please refer to website for current technical specification)


Wattage	No LED's	V	Lms (P/200mm)	Weight (Kg)
TROS8wLED	6	24	500	2.0 Kg
TROS16wLED	6	24	1500	2.0 Kg

Available in colour temp 3000/4000/5000K

### Suffix

/W	White Body
/B	Black Body
/O	Opal Diffuser
/P	Clear Reeded Diffuser
/PC	Integral Photocell
/EM3	Integral Emergency
/SS	Security Screws
/SD	Security Driver
/RC-KIT	Recess Mount Kit
/M-Wave	Microwave Motion Detection option
/LIFE	Long Life Fluorescent option

\*Eyelid option on request



 Cut out 380mm x 155mm  
Recessed version

