


V-LEXX ANGLE SECURE



- IP44/54 – IK10++
- Metal End Cap
- Clear Prismatic Polycarbonate Controller
- Vandal Resistant Design
- Stainless Steel Security Screws
- Removable High Frequency Gear-Tray
- White Metalwork Standard
- Other RAL Colour Options



DESCRIPTION

A shallow cornice mounted robust luminaire incorporating a clear reeded extruded polycarbonate diffuser, supported along its length by the luminaire body & held captive by die cast aluminium end cap. Fixed by stainless steel security screws. Removable high frequency gear tray. Standard luminaire IP44, optional gasket to IP54

APPLICATION

Car Parks, Medium Security Areas, Pedestrian Walk Ways, Schools, Public Areas, Local Authority Areas etc

RANGE AVAILABLE

Catalogue No.	Description	Length	Weight (Kg)	Dimensions
VDXA114	1 x 14w/HF/T5	2ft/ 600mm	4.0 Kg	
VDXA128	1 x 28w/HF/T5	4ft/1200mm	7.0 Kg	
VDXA154	1 x 54w/HF/T5	4ft/1200mm	7.0 Kg	
VDXA135	1 x 35w/HF/T5	5ft/1500mm	8.0 Kg	
VDXA149	1 x 49w/HF/T5	5ft/1500mm	8.0 Kg	
VDXA214	2 x 14w/HF/T5	2ft/ 600mm	4.0 Kg	
VDXA228	2 x 28w/HF/T5	4ft/1200mm	7.0 Kg	
VDXA254	2 x 54w/HF/T5	4ft/1200mm	7.0 Kg	
VDXA235	2 x 35w/HF/T5	5ft/1500mm	8.0 Kg	
VDXA249	2 x 49w/HF/T5	5ft/1500mm	8.0 Kg	

Suffix

/HFD	High Frequency Dimmable Gear
/EM3	3 hour Maintained Emergency
/NL	Night Lite
/SD	Security Key
/IP54	IP54 Version

*Other RAL colours on request

*Stainless Steel version available for special applications

080

VANDAL RESISTANT SURFACE FLUORESCENT RANGE