




# VICTORY

## CORROSION RESISTANT

**ZONE 2 VERSION CURRENTLY UNDER TEST  
ATEX & IEC EX-SIRA**



- IP65
- Corrosion Resistant
- Polycarbonate Body & Clear Reeded Controller
- Removable High Frequency Gear Tray
- Optional Vandal Resistant Stainless Steel Diffuser Clips
- 20mm Cable Entry End Holes c/w Sealing Plugs
- Microwave Motion Detection option
- Longlife 50,000 hrs Fluorescent options
- LED Option



### DESCRIPTION

Industrial luminaire suitable for many arduous applications. Nylon toggle clips as standard, stainless steel security toggle clips (optional). Polycarbonate clear reeded controller. End wiring facility.

### APPLICATION

Wash Rooms, Under Canopy, Warehouses, Boiler Rooms etc.

### RANGE AVAILABLE

Catalogue No.	Description	Weight (Kg)	Dimensions
VCT114	1x14w HF T5 2ft/ 666mm	1.9 Kg	
VCT128	1x28w HF T5 4ft/1276mm	2.9 Kg	
VCT154	1x54w HF T5 4ft/1276mm	2.9 Kg	
VCT135	1x35w HF T5 5ft/1576mm	3.8 Kg	
VCT149	1x49w HF T5 5ft/1576mm	3.8 Kg	
VCT214	2x14w HF T5 2ft/ 666mm	2.2 Kg	
VCT228	2x28w HF T5 4ft/1276mm	4.5 Kg	
VCT254	2x54w HF T5 4ft/1276mm	4.5 Kg	
VCT235	2x35w HF T5 5ft/1576mm	6.2 Kg	
VCT249	2x49w HF T5 5ft/1576mm	6.2 Kg	

### LED Versions (Please refer to website for current technical specification)

Wattage p/mtr	No LED's	Voltage	Lms
(Compromising of 10 qty x 100mm sections of 2.3w)			
VCT23wLED	60	24v/240v	2100 } per lampway

Various T5/T8 type LED Tubes on request  
Available in colour temp 3000/4000/5000k

### Suffix

/ZONE1	Zone1 Hazardous Area
/EM3	3 hour Integral Maintained Emergency
/VRC	Stainless Steel Vandal Resistant Clips
/M-Wave	Microwave Motion Detection option

