



WYEVALE II



**NOMS
Anti
Ligature**

 Economical	 LED	 IP65	 IK10-150J
 Dimmable	 NOMS STD/E/ SPEC/021	 Anti Ligature	 Optional Motion Detection
 Night Light	<p>* National Offender Management Service - For Standard Cellular Accommodation ** Anti Ligature must be correctly installed using 'Anti Pick' Mastic</p>		

- For Standard Cellular Accommodation NOMS STD/E/SPEC/021*
- Anti Ligature Must be correctly installed using 'Anti Pick' Mastic
- Fully Welded Steel Body
- Heavy Gauge Regressed Bezel & Captive Polycarbonate Diffuser
- Countersunk Stainless Steel Security Screw Fixing
- Removable LED Gear Tray



Linear LED Technical Information

Please refer to website for current LED technical specification

Order Code	Length	Lumens	Im/W		Colour Temp	Ra	Weight
			HE	HO			
WYE2 1.3	2.6 700	1300lm	2600lm	115	3000K/4000K	>80	6.0
WYE2 1.9	3.9 1000	1950lm	3900lm	112	3000K/4000K	>80	8.0
WYE2 2.6	5.2 1300	2600lm	5200lm	110	3000K/4000K	>80	10.0
WYE2 3.2	6.5 1600	3250lm	6500lm	108	3000K/4000K	>80	12.0


* NOMS = WYE2-NOMS1.9+1.9LED-3K/W/F/NL-LED-3K

Specific higher/lower lumen packages on request (above are LED comparable to T5 lamp options)

***RGB Colour Change LED & **Tuneable White LED options**

Ordering Options

Description	Suffix Ordering Code
Exterior Fully Weatherproof Version	/EXT
Dimmable Options (DALI/1-10v/Sw-240v/Corridor)	/DALI / 1-10v / SW-240v / CORR
Integral 3hr Emergency or 3hr Self Test	/EM3 or /EM3-SELF
Microwave Motion Detection	/M-Wave
Night Light	/NL
Frosted Diffuser	/F
Clear Stippled Diffuser	/P
Security Driver/Key	/SD
Stainless Steel Version (316/304/430 Grades)	On Request
LED Linear Tube Gear Tray (240v Mains)	/GT-LEDT5
Fluorescent Lamp Version	/T5 or /T8 On Request



Standard Fixing Detail

- 4qty x 6mm Ø Back Body Corner Mounting Holes
- 1qty x 20mm Ø Back Body Centre Cable Entry Hole

Custodial