




BOREAL BOLLARD

EXTERIOR BOLLARD RANGE



- IP54 – IK10
- All Moulded Polycarbonate Construction
- Clear Polycarbonate Lens
- Louvre Stack
- Black Extruded Moulded Body (Non Corrosive)
- Root or Flange Mount
- Discharge or Compact PL Lamp options
- Longlife 50,000 hrs Fluorescent options
- LED Option



DESCRIPTION

A decorative bollard with clear polycarbonate lens & louvre stack, non corrodible construction. Root or flange plate mount options. Optional overall heights on request.

APPLICATION

Commercial & Industrial Locations, Retail Parks, Residential Developments, Pathways Ideally suited to public circulation areas & exposed amenity lighting applications.

RANGE AVAILABLE

Catalogue No.	Description	Weight (Kg)	Dimensions
BOR50S	50w SON	10 Kg	
BOR70S	70w SON	10 Kg	
BOR50MH	50w Metal Halide	10 Kg	
BOR70MH	70w Metal Halide	10 Kg	
BOR32	26w HF/TC-DE	10 Kg	
BOR26	32w HF/TC-TEL	10 Kg	
BOR42	42w HF/TC-TEL	10 Kg	
BOR/RT	Root Mounting Accessory		

LED Versions (Please refer to website for current technical specification)

Wattage	No LED's	mA	Lms	Weight (Kg)
BOR12wLED	12	350	900	10.0 Kg
BOR18wLED	12	500	1400	10.0 Kg
BOR24wLED	12	700	2200	10.0 Kg

Available in colour temp 3000/4000/5000K

Suffix

/FL	Flange Mounting Plate Version
/EM3	Emergency PL Available
/LIFE	Long Life Fluorescent option

