

# BOSTON DOME TOP BOLLARD



## VANDAL RESISTANT BOLLARD RANGE



- IP65 – IK10 ++
- Cast Aluminium Dome Head
- Clear Polycarbonate Lens
- Anodised Aluminium Louvre Stack
- Heavy Gauge Steel Tube, Root or Flange Mounted
- Optional VANDACOAT offering enhanced Corrosion/Vandal & Graffiti Resistant Coating System
- Discharge or Compact PL Lamps options
- Black Paint Finish as standard
- Various RAL colour options on request
- Longlife 50,000 hrs Fluorescent options
- LED Option



### DESCRIPTION

A robust decorative bollard with clear polycarbonate lens & louvre stack, with alloy dome top. Available either root or flange mounted. Optional overall heights on request.

### APPLICATION

Commercial & Industrial Locations, Retail Parks, Residential Developments, Pathways Ideally suited to public circulation areas & exposed amenity lighting applications.

### RANGE AVAILABLE

Catalogue No.	Description	Weight (Kg)	Dimensions
BOSD50S	50w Son	13.0 Kg	
BOSD70S	70w Son	13.0 Kg	
BOSD50MH	50w Metal Halide, HIPE	13.0 Kg	
BOSD70MH	70w Metal Halide, HIPE	13.0 Kg	
BOSD26	26w HF/TC-DEL	12.5 Kg	
BOSD32	32w HF/TC-TEL	12.5 Kg	
BOSD42	42w HF/TC-TEL	12.5 Kg	

### LED Versions (Please refer to website for current technical specification)

Wattage	No LED's	mA	Lms	Weight (Kg)
BOSD12wLED	12	350	900	13.0 Kg
BOSD18wLED	12	500	1400	13.0 Kg
BOSD24wLED	12	700	2200	13.0 Kg

Available in colour temp 3000/4000/5000K

### Suffix

/RT	Root Mounting Version
/FL	Flange Mounting Plate Version
/EM3	Integral Emergency - PL lamps only
/180°	180° Light Baffle
/LIFE	Long Life Fluorescent option
/VCOAT	VANDACOAT Enhanced External Coating system

\*Other RAL colour options available on request

