


ENERGY NOVELLA

RECESSED DOWNLIGHT RANGE



- IP20/44/65
- IP65 – IK10++ Security Bezel (optional)
- Selection of Attachments
- High frequency Control Gear
- Removable Gear Housing
- Adjustable Side arm Brackets
- Longlife 50,000 hrs Fluorescent Lamps
- High Quality Aluminium Reflector
- LED Options



DESCRIPTION

General purpose recessed downlight range, white metal bezel as standard. Removable high frequency control gear housing. Available with a range bezel / glass attachments. IP65 IK10+ Security Bezel option c/w clear polycarbonate panel & stainless steel security screws. LED & longlife fluorescent options.

APPLICATION

Offices, Corridors, Foyers, Restaurants, Shopping Malls, Showrooms.

RANGE AVAILABLE

Catalogue No.	Description	Weight (Kg)	Dimensions
NRGN118PL	18w HF TC-DEL	1.5 Kg	
NRGN126PL	26w HF TC-DEL	1.5 Kg	
NRGN218PL	2x18w HF TC-DEL	1.5 Kg	
NRGN226PL	2x26w HF TC-DEL	1.5 Kg	

LED Versions (Please refer to website for current technical specification)

Wattage	No LED's	mA	Lms	Weight (Kg)
NRGN16wLED	60	500	1500	1.5 Kg
NRGN23wLED	60	700	2100	1.5 Kg
NRGN26wLED	72	700	2500	1.5 Kg
NRGN24wLED/HO	24	700	2900	1.5 Kg
NRGN48wLED/HO	24	1400	4800	1.5 Kg

various Optics available on request

Note EM3 version c/w 4 x 1 w LED
Available in colour temp 3000/4000/5000K

Suffix

/HFD	High Frequency Dimmable
/EM3	3 hour Remote Maintained Emergency
/IP44	IP44 Bezel Attachment
*/IP65/SS	IP65 Security Bezel Attachment
/ATT1	Drop Glass – Outer Frosted Attachment
/ATT2	Drop Glass – Inner Frosted Attachment
/ATT3	Frosted Glass Attachment
/ATTC	Chrome Bezel Attachment
/ATTS	Satin Chrome Attachment
/LIFE	Long Life Fluorescent option

*Various RAL colour options available

