


ETON SECURE

SURFACE RANGE



- IP44
- White Steel Body
- Moulded Plastic End Cap
- Secure Bezel/Clear Polycarbonate Panel
- Stainless Steel Security Screws
- Aluminium Low Brightness Louvre
- High Frequency Control Gear
- Microwave Motion Detection option
- Longlife 50,000 hrs Fluorescent options
- LED Option



DESCRIPTION

A range of decorative surface or suspended luminaires. Fabricated quality steel body, moulded end cap. Captive clear polycarbonate panel fixed with stainless steel security screws. Anodised aluminium louvre.

APPLICATION

Offices, Foyers, Corridors, Classrooms, Hospitals, Dining Areas, Prison Association Areas etc.

RANGE AVAILABLE

Catalogue No.	Description	Length (mm)	Weight (Kg)	Dimensions
ETNS128	1x28w HF T5	4ft/1250mm	6.8 Kg	
ETNS154	1x54w HF T5	4ft/1250mm	6.8 Kg	
ETNS135	1x35w HF T5	5ft/1550mm	6.8 Kg	
ETNS149	1x49w HF T5	5ft/1550mm	6.8 Kg	
ETNS228	2x28w HF T5	4ft/1250mm	6.8 Kg	
ETNS254	2x54w HF T5	4ft/1250mm	6.8 Kg	
ETNS235	2x35w HF T5	5ft/1550mm	6.8 kg	
ETNS249	2x49w HF T5	5ft/1550mm	6.8 Kg	

LED Versions (Please refer to website for current technical specification)

Wattage p/mtr	No LED's	Voltage	Lms
(Compromising of 10 qty x 100mm sections of 2.3w) ETNS23wLED	60	24v/240v	1900 } per lampway

Various T5/T8 type LED Tubes on request
Available in colour temp 3000/4000/5000k

Suffix

/HFD	High Frequency Dimmable Control Gear
/EM3	3 hour Maintained Emergency
/NL	Night Lite
/SD	Security Driver
/M-Wave	Microwave Motion Detection option
/LIFE	Long Life Fluorescent option

