

LIBERTY DROP INDIRECT RECESSED MODULAR



- IP20
- Central Curved Perforated Metal Diffuser
- Indirect Lighting Control
- Powder Coated Paint Finish
- Injection Moulded End Caps (White or Chrome)
- Suitable for 15/25 Exposed 'T' Grid Ceilings
- Optional Extra Bezel for Plasterboard Ceilings
- High Frequency Control Gear
- Microwave Motion Detection option
- Longlife 50,000 hrs Fluorescent options
- LED Option



DESCRIPTION

Flagship range of recessed luminaires designed to meet present day standards. Curved perforated metal louvre providing upward light onto 'gull' reflector directing light across the ceiling and downwards. LED option on request & long life fluorescent options.

APPLICATION

Commercial Office Lighting, Meeting Rooms, Computer Rooms, Retail Areas, Reception, Medical Areas etc

RANGE AVAILABLE

Catalogue No.	Description	Weight (Kg)	Dimensions
LIBDM155	1x55w HF TC-L	6.3 Kg	
LIBDM255	2x55w HF TC-L	6.3 Kg	
LIBDM214	1x14w HF T5	6.3 Kg	
LIBDM224	2x24w HF T5	6.3 Kg	

LED Versions (Please refer to website for current technical specification)

Wattage p/mtr	No LED's	Voltage	Lms	Weight (Kg)
(Compromising of 10 qty x 100mm sections of 2.3w) LIBDM23wLED	60	24v/240v	2100 } per lampway	6.3 Kg

Various T5/T8 type LED Tubes on request
Available in colour temp 3000/4000/5000k

Suffix

/HFD	High Frequency Dimmable Gear
/EM3	3 Hour Maintained Emergency
/ATT	Plasterboard Mounting Kit
/ECW	White End Cap
/ECC	Chrome End Cap
/M-Wave	Microwave Motion Detection option
/LIFE	Long Life Fluorescent option

