


# MAYFAIR ROUND DISH



## AMENITY LIGHTING



- IP65 – IK10
- Polycarbonate Body & Diffuser
- Wall, Ceiling or Recessed Mount
- Removable Hinged High Frequency Gear Tray
- Opal, Frosted or Clear Prismatic Diffuser
- White or Black Base
- Microwave Motion Detection option
- Longlife 50,000 hrs Fluorescent options
- LED Options



### DESCRIPTION

All polycarbonate enclosure fitted with Pozi – drive Diffuser fixing screws as standard. Torx security screws optional. Facility for side entry conduit. Semi-Recess Kit available as optional extra.

### APPLICATION

Amenity areas, Lobbies, Corridors, Store Rooms, General Areas.

### RANGE AVAILABLE

Catalogue No.	Description	Weight (Kg)	Dimensions
MAYR162D	16w 2D HF TC-DD	1.5 Kg	
MAYR282D	28w 2D HF TC-DD	1.5 Kg	
MAYR382D	38w 2D HF TC-DD	1.5 Kg	

### LED Versions (Please refer to website for current technical specification)

Wattage	No LED's	mA	Lms	Weight (Kg)
MAYR11wLED	60	350	1000	1.5 Kg
MAYR16wLED	60	500	1500	1.5 Kg
MAYR23wLED	60	700	2100	1.5 Kg

note EM3 version c/w 4 x 1w LED  
Available in colour temp 3000/4000/5000K

### Suffix

/W	White Body
/B	Black Body
/DP	Dish Prismatic Diffuser
/DO	Dish Opal Diffuser
/DF	Dish Frosted Diffuser
/PC	Integral Photocell
/SS	Fitted with Security Screws
/SD	Security Screwdriver
/EM3	3 hour Integral Emergency – (excluding 38w2D)
/RC-KIT	Semi - Recessing Kit cut out 290mm Ø
/M-Wave	Microwave Motion Detection option
/LIFE	Long Life Fluorescent option

\* Eyelid option on request

