

SHETLAND POST TOP



EXTERIOR LIGHTING RANGE



- IP65 – IK10++
- Non Corrosive Vandal Resistant
- 5 mm Thick Opal Polycarbonate Visor
- Integral Gear Tray c/w Easy Access Connections
- Two Body sizes
- Integral Photo Cell (optional)
- To Fit 76mm Ø Post
- NEMA Socket option/Mini Photocell option
- Large Canopy Top Hat (optional)
- Moulded Black Poly Prop Base & Lid
- LED Option



Standard

Large

DESCRIPTION

Extremely tough black Poly Prop heavy duty base & lid with 76 mm diameter spigot entry. Integral control gear. Optional Large black top hat canopy to reduce upward light content. Optional inner 180° light shield.

APPLICATION

Vandal Resistant Areas, Parks, Drives, Roadways, Coastal Regions, Saline Atmospheres, Housing Estates, Access Roads, Car Parks.

RANGE AVAILABLE

Catalogue No.	Description	Weight (Kg)	Dimensions
STANDARD			
SHE50S	50w SON	4.5 Kg	
SHE70S	70w SON	4.5 Kg	
SHE100S	100w SON	4.5 Kg	
SHE50MM			
SHE50MM	50w HIPE	4.5 Kg	
SHE70MM	70w HIPE	4.5 Kg	
LARGE			
SHEL100S	1X100w SON	6.0 Kg	
SHEL100MH	1X100w HIPE	6.0 Kg	
SHEL150S	1X150w SON	6.0 Kg	
SHEL150MH	1X150w HIPE	6.0 Kg	

LED Versions (Please refer to website for current technical specification)

Wattage	No LED's	mA	Lms	Weight (Kg)
SHE24wLED	24	700	2500	4.0 Kg
SHE48wLED	24	1400	4800	4.0 Kg

Available in colour temp 3000/4000/5000K

Suffix

/PC	Mini Photo-Cell
/PS	NEMA photocell socket only
/SKY.CAN	Black Top Canopy 520 diameter
/L/Shield	180° Inner Light Shield

*Refer to page 48 for spigot adapters

