



SKYE POST TOP

EXTERIOR LIGHTING RANGE



- IP65 – IK10++
- Non Corrosive Vandal Resistant
- 5 mm Thick Clear Reeded Polycarbonate Visor
- Integral Gear Tray c/w Easy Access Connections
- Two Body sizes
- Integral Photo Cell (optional)
- To Fit 76mm Ø Post
- NEMA Socket option/Mini Photocell option
- Large Canopy Top Hat (optional)
- Moulded Black Poly Prop Base & Lid
- LED Option



DESCRIPTION

Extremely tough black Poly Prop heavy duty base & lid with 76 mm diameter spigot entry. Integral control gear. Optional Large black top hat canopy to reduce upward light content. Optional inner 180° light shield.

APPLICATION

Vandal Resistant Areas, Parks, Drives, Roadways, Coastal Regions, Saline Atmospheres, Housing Estates, Access Roads, Car Parks.

RANGE AVAILABLE

Catalogue No.	Description	Weight (Kg)	Dimensions
STANDARD			
SKY50S	50w SON	4.5 Kg	
SKY70S	70w SON	4.5 Kg	
SKY100S	100w SON	4.5 Kg	
SKY50MH			
SKY50MH	50w HIPE	4.5 Kg	
SKY70MH	70w HIPE	4.5 Kg	
LARGE			
SKYL100S	1X100w SON	6.0 Kg	
SKYL100MH	1X100w HIPE	6.0 Kg	
SKYL150S	1X150w SON	6.0 Kg	
SKYL150MH	1X150w HIPE	6.0 Kg	

LED Versions (Please refer to website for current technical specification)

Wattage	No LED's	mA	Lms	Weight (Kg)
SKY24wLED	24	700	2500	4.0 Kg
SKY48wLED	24	1400	4800	4.0 Kg

Available in colour temp 3000/4000/5000K

Suffix

/PC	Mini Photo-Cell
/PS	NEMA photocell socket only
/SKY.CAN	Black Top Canopy 520 diameter
L/Shield	180° Inner Light Shield

*Refer to page 48 for spigot adapters

