




SOFTLITE

SURFACE UPLIGHT RANGE



- IP20
- Perforated Curve Profile Metal Body with Opal Inner Lining
- White Paint Finish
- Up – Light, Wall Fixture
- High Frequency Control Gear
- Other RAL Colours On Request
- Microwave Motion Detection option
- Longlife 50,000 hrs Fluorescent options
- LED Option



DESCRIPTION

Designed for compatibility with today's commercial interiors. This wall mounted version gives a combination of upward & restricted downward light to produce an efficient optical system. LED version on request & long life fluorescent options.

APPLICATION

Offices, Corridors, Foyers, Hotels etc

RANGE AVAILABLE

Catalogue No.	Description	Weight (Kg)	Dimensions
SFT155	1x55w HF TC-L	4.5 Kg	
SFT255	2x55w HF TC-L	4.5 Kg	
SFT214	2x14w HF T5	4.5 Kg	
SFT224	2x24w HF T5	4.5 Kg	

LED Versions (Please refer to website for current technical specification)

Wattage p/mtr	No LED's	Voltage	Lms	Weight (Kg)
(Compromising of 10 qty x 100mm sections of 2.3w) SFT23wLED	60	24v/240v	2100 } per lampway	4.5 Kg

Various T5/T8 type LED Tubes on request
Available in colour temp 3000/4000/5000k

Suffix

/HFD	High Frequency Dimmable Gear
/EM3	3 Hour Maintained Emergency
/M-Wave	Microwave Motion Detection option
/LIFE	Long Life Fluorescent option

*Other RAL colours on request

