




TITAN III

(SAFER CELL) ANTI LIGATURE CORNICE RANGE



*NOMS STD/E/SPEC/022/Cellular & Safer Cell Accommodation

Anti Ligature Note: When correctly installed against wall and ceiling, using 'Anti Pick' Mastic.

- IP65 - IK10 ++
- Fully Welded Fabricated Steel Body Cornice Luminaire
- Regressed Gasketed Bezel which removes the need to disturb anti pick mastic
- Captive Diffuser Panel
- 3 x Compartment Cable Tray
- Torx Security Screw
- Removable High Frequency Gear Tray
- Longlife 50,000 hrs Fluorescent options
- LED Option



DESCRIPTION

A range of vandal resistant, anti ligature luminaires. The fittings are 'anti ligature' for use in sensitive areas & designed to run 'wall to wall' and can be adjusted in length. Can be supplied as individual/stand alone fittings. Bezel/Diffuser removes without disturbing anti pick mastic. LED versions available on request.

APPLICATION

For use in Prison 'Safer Cell' and sensitive areas, Police Stations, Public Areas where a high degree of vandal resistance is required. Manufactured to length to suit application.

RANGE AVAILABLE

Catalogue No.	Description	Dimension (mm)	Weight (Kg)	Dimensions
TTNN114	1x14w HF T5	2ft/ 960mm	12 Kg	
TTNN128	1x28w HF T5	4ft/ 1430mm	18 Kg	
TTNN135	1x35w HF T5	5ft/ 1730mm	22 Kg	
TTNN149	1x49w HF T5	5ft/ 1730mm	22 Kg	
TTNN154	1x54w HF T5	4ft/ 1430mm	18 Kg	
TTNN214	2x14w HF T5	2ft/ 960mm	12 Kg	
TTNN228	2x28w HF T5	4ft/ 1430mm	18 Kg	
TTNN235	2x35w HF T5	5ft/ 1730mm	22 Kg	
TTNN249	2x49w HF T5	5ft/ 1730mm	22 Kg	
TTNN254	2x54w HF T5	4ft/ 1430mm	18 Kg	

*TTNN128/154/7 1x28/1x54w&1x7w Night Light *{Safer cell requirement} Dimensions tbc (further info on request)

LED Versions (Please refer to website for current technical specification)

Wattage p/mtr	No LED's	Voltage	Lms
(Compromising of 10 qty x 100mm sections of 2.3w)			
TTNN23wLED	60	24v/240v	2100 } per lampway

Various T5/T8 type LED Tubes on request
Available in colour temp 3000/4000/5000k

Suffix

/O	Opal Diffuser
/P	Clear Stippled Diffuser
/GRP	Glass Reinforced Panel
/HFD	High Frequency Dimmable
/EM3	3 Hour Maintained Emergency
/NL	Night Light
/SD	Security Driver
/M-Wave	Microwave Motion Detection option
/LIFE	Long Life Fluorescent option

