




TROJAN LARGE

AMENITY / EMERGENCY LIGHTING RANGE



- IP65 – IK10
- Injection Moulded Polycarbonate Luminaire
- Opal or Clear Reeded Diffuser
- Removable High Frequency Gear Tray
- Stainless Steel Torx Captive Screw
- Conduit Entry
- Microwave Motion Detection option
- Longlife 50,000 hrs Fluorescent options
- LED Options



DESCRIPTION

Rectangular slim design. Bulkhead luminaire with 4 No Torx stainless steel screws. Removable high frequency gear tray for low energy fluorescent lamps, maintained & non maintained emergency versions. Conduit entry. Recessed version available.

APPLICATION

Interior & Exterior usage, Lobbies, Corridors, Multi Storey Car Parks, Stairs, Toilets etc

RANGE AVAILABLE

Catalogue No.	Description	Weight (Kg)	Dimensions
TROL218	2x18w HF TC-DEL	4.0 Kg	
TROL226	2x26w HF TC-DEL	4.0 Kg	
TROL1282D	1x28w HF TC-DD	4.0 Kg	
TROL1382D	1x38w HF TC-DD	4.0 Kg	
TROL132	1x32w HF TC-TEL	4.4 Kg	
TROL142	1x42w HF TC-TEL	4.4 Kg	

LED Versions (Please refer to website for current technical specification)

Wattage	No LED's	mA	Lms	Weight (Kg)
TROL16wLED	60	500	1500	4.0 Kg
TROL23wLED	60	700	2500	4.0 Kg
TROL26wLED	72	700	2500	4.0 Kg
TROL24wLED/HO	24	700	2900	4.0 Kg


various Optics available on request

note EM3 version c/w 4 x 1w LED
Available in colour temp 3000/4000/5000K

Suffix

/W	White Body
/B	Black Body
/O	Opal Diffuser
/P	Clear Reeded Diffuser
/F	Frosted Diffuser
/PC	Integral Photocell
/EM3	Integral Emergency – 28 & 38w2D only
/SS	Security Screws
/SD	Security Driver
/RC-KIT	Recess Mount Kit – cut out 375mm x 285mm
/M-Wave	Microwave Motion Detection option
/LIFE	Long Life Fluorescent option

*Eyelid option on request



Cut out 375mm x 285mm
Recessed version

