

# WYEVALE 660 x 660



## VANDAL RESISTANT SURFACE ANTI LIGATURE RANGE



**Anti Ligature Note:** When correctly installed against ceiling, using 'Anti Pick' Mastic.

- IP65 – IK10++
- Optional VANDACOAT offering enhanced Corrosion/Vandal & Graffiti Resistant Coating System
- Fully Welded Fabricated Steel Body
- Regressed Gasketed Bezel
- Captive Opal or Clear Stippled Polycarbonate Panel
- Stainless Steel Torx Security Screw Fixing
- Removable High Frequency Gear Tray
- Other RAL Colour Options
- Microwave Motion Detection option
- Longlife 50,000 hrs Fluorescent options
- LED Option



### DESCRIPTION

Robust slim 70mm surface mounted enclosed luminaire, anti ligature construction with texture white paint finish as standard. Bezel/ Diffuser removes without disturbing anti pick mastic. LED versions available on request & long life fluorescent versions

### APPLICATION

Pharmaceutical Environments, Hospitals, Secure Units, Kitchens, Laboratories, Clean Rooms etc.

### RANGE AVAILABLE

Catalogue No.	Description	Dimension (mm)	Weight (Kg)	Dimensions
WYE6314	3x14w HF T5	660mmx660mm	10 Kg	
WYE6414	4x14w HF T5	660mmx660mm	10 Kg	
WYE6324	3x24w HF T5	660mmx660mm	10 Kg	
WYE6424	4x24w HF T5	660mmx660mm	10 Kg	
WYE6328	3x28w HF T5	1200mmx600mm	14 Kg	
WYE6428	4x28w HF T5	1200mmx600mm	14 Kg	
WYE6354	3x54w HF T5	1200mmx600mm	14 Kg	
WYE6454	4x54w HF T5	1200mmx600mm	14 Kg	

**LED Versions** (Please refer to website for current technical specification)

Wattage p/mtr	No LED's	Voltage	Lms
(Compromising of 10 qty x 100mm sections of 2.3w) WYE623wLED	60	24v/240v	1900 } per lampway

Flat LED panel on request  
Various T5/T8 type LED Tubes on request  
Available in colour temp 3000/4000/5000k

#### Suffix

/P	Clear Stippled Diffuser
/O	Opal Diffuser
/HFD	High Frequency Dimmable Gear
/EM3	3 hr Maintained Emergency
/NL	Night Light
/SD	Security Driver
/M-Wave	Microwave Motion Detection option
/LIFE	Long Life Fluorescent option
/VCOAT	VANDACOAT Enhanced External Coating system

\*Stainless Steel version on request

